

SOLID

ALLIANCE Multi-Operator DAS DMS-1200 DAS Management System Product Specifications / Parts List

The screenshot displays the DMS-1200 DAS Management System interface. At the top, a physical device is shown with the SOLiD logo and 'DMS-1200REL6' label. The main interface is divided into several sections:

- System Information:** Displays BIU Name (Kvvin BIU), F/W Version (6.2), Temperature (35°C), and Low/High (10/70). It also shows External ALM status.
- Event Log:** A table listing 13 events with columns for No., Type, Level, BIU, Device, Name, Message, Time Received, and Time Cleared. The events include security events (login, auto logout) and alarms (Link Fail, MDBU Link Fail, PD Fail).
- Firmware Download:** A table listing 4 files for download, including BIU, NHR0U, APPLICATION, and BATCH files.
- System Configuration:** Shows details for three MDPU units (MDPU#1, MDPU#2, MDPU#3) with their respective F/W versions and temperatures.

SOLiD's DMS-1200 provides an enterprise level interface between the fiber optic Distributed Antenna System (DAS) and your Network Operations Center (NOC). The DMS-1200 gathers vital system information and alarm data from the DAS network and transmits via SNMP to the designated NOC facility for monitoring.

The DMS-1200 keeps downtime to a minimum and ensures your SOLiD system remains reliable. Comprehensive DAS system health checks are continually conducted and changes in status and alarm detection are reported in real time.


Whether you monitor with your own network computer or utilize a sophisticated carrier-grade NOC, the DMS-1200 is the interface that will perform to the highest of standards in any application.

Features


The DMS-1200 provides these management functions for the DAS network:

- Centralized management for devices and auto discovery of the DAS network topology
- Web-based management over HTTP/HTTPS for up to 20 iBIU units
- Quick and Easy Configuration using EasySET commissioning and auto Power Distribution
- Configurable SNMP V2/V3 traps sent to NOC
- Support for private enterprise MIB files provided for SNMP traps
- Configurable IP settings for DMS and NOC(s)
- Auto assign iBIU's IP addresses
- Real-time alarm monitoring and collection
- Alarm Control: hysteresis, alert level, troubleshooting, masking, email notification
- Programmable dry contacts
- DMS-1200 system upgrades via the web or USB flash
- Firmware upgrade for all devices from DMS
- Custom filtering and data export for Inventory reports, Alarm logs, Event logs, Trend logs
- Historical trend data for devices
- Automatic or manual backup and for restoring device settings

The DMS-1200 communicates with the DAS through the system's BTS Interface Units (iBIUs) over a standard TCP/IP connection or secure HTTP / HTTPS protocol. Alarms and device status are transmitted to the NOC via SNMPv2/v3. You can access the DMS-1200 functions either onsite or remotely. The DMS-1200 server is based on the Ubuntu 12.04 LTS operating system. The user interface can be viewed in any standard web browser. Connecting multiple iBIUs requires a Gigabit Ethernet switch.



Specifications



Parameter	Specification
Available Interface Ports	One LAN Ethernet Port each for WAN, iBIU connection, local console port One LAN Ethernet Port reserved for future use. Two USB Ports (USB rating: 5v, 0.5amp)
External Alarm Connector	Programmable dry contacts
Serial Interface	1 RS232
Front Panel Controls / LED Indicators	System RESET button Power ON/OFF button LEDs show status for: Power, System Activity, Network Activity, High Temp Warning
Power Specifications	AC Voltage: 100-240V, 60-50Hz Amperage: 2 amps maximum Power consumption: 80 W at Full Load 6ft. cord with NEMA 5-15 plug (included)
Dimensions (W x H x D mm)	Rack-mountable (19-inch, 1U) 16.8"W (fits 19" rack) x 1.75"H (1U) x 14"D 426 mm x 43 mm (1U) x 356 mm
Weight	14 lbs (6.4 kg)
Operating Environment	Operating Temp: 50° to 95° F (10 to 35°C). Humidity Range: 8 ~ 90% non-condensing
Power Safety / Approvals	USA: UL Listed & FCC. Canada: CUL Listed. Germany: TUV Certified. Europe/CE Mark: EN 60950/IEC 60950-Compliant. CCC Certified

Part Numbers

DMS-1200 Description	Part Number
DAS Management System (DMS) for ALLIANCE - For use with Rel. 6	DMS_1200



SOLID Gear, Inc.
800 Klein Road, Suite 200
Plano, TX 75074
PHONE: 888.409.9997
EMAIL: sales@solid.com
WEB: www.solid.com



ISO9001 **ISO14001** **ISO45001**
CERTIFIED CERTIFIED CERTIFIED